

09/693511

**LOCATION-BASED IDENTIFICATION FOR USE IN A
COMMUNICATIONS NETWORK**

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims priority from U.S. Provisional Patent Application Serial Number 60/161,093, the contents of which are incorporated by reference.

FIELD OF THE INVENTION

The present invention relates generally to an identification process within a communications network and, more particularly, to a method and apparatus for implementing location-based identification in a communications network.

BACKGROUND OF THE INVENTION

While desktop computers generally remain a part of the same network for a substantial period of time, laptops, handhelds, personal digital assistants (PDAs), cellphones or other portable computers (collectively "portable computers") are specifically designed to be transportable. As such, portable computers are connected to different networks at different times depending upon the location of the computer. In a common example in which the portable computer serves as an employee's desktop computer, the portable computer is configured to communicate with their employer's network, i.e., the enterprise network. When the employee travels, however, the portable computer may be connected to different networks that communicate in different manners. In this regard, the employee may connect the portable computer to the network maintained by an airport, a hotel, a cellular telephone network operator or any other locale in order to access the enterprise network, the Internet or some other on-line service. The portable computer is also commonly brought to the employee's residence where it is used to access various networks, such as, the enterprise network, a home network, the Internet and the like. Since these other networks are configured somewhat differently, however, the portable computer must also be reconfigured in order to properly communicate with these other networks. Typically, this configuration is performed by the user each time that the portable computer is connected to a different network. As will be apparent, this repeated reconfiguration of the portable computer is not only quite time

consuming, but is also prone to errors. The reconfiguration procedure may even be beyond the capabilities of many users or in violation of their employer's IT policy.

A universal subscriber gateway device has been developed by Nomadix, L.L.C. of Westlake Village, California and is described in detail in United States Patent Application Nos. 08/816,174, entitled "Nomadic Router", filed on March 12, 1997, in the name of inventors Short et. al.; 09/458,602, entitled "Systems and Methods for Authorizing, Authenticating and Accounting Users Having Transparent Computer Access to a Network Using a Gateway Device", filed on December 08, 1999, in the name of inventors Pagan et. al.; and 09/458,569, entitled " Systems and Methods for Redirecting Users Having Transparent Computer Access to a Network Using a Gateway Device Having Redirection Capability" filed on December 08, 1999, in the name of inventors Short et. al. These applications have been assigned to the same assignee as the present invention and the contents of these applications are expressly incorporated herein by reference as if setforth fully herein.

The gateway device serves as an interface connecting the user/subscriber to a number of networks or other online services. For example, the gateway device can serve as a gateway to the Internet, the enterprise network, or other networks and/or on-line services. In addition to serving as a gateway, the gateway device automatically adapts to the protocols and other parameters of the host, in order that it may communicate with the new network in a manner that is transparent both to the user/subscriber and the new network. Once the gateway device has appropriately adapted to the user's host, the host can appropriately communicate via the new network, such as the network at a hotel, at home, at an airport, or any other location, in order to access other networks, such as the enterprise network, or other online services, such as the internet.

The portable computer user/subscriber, and more specifically the remote or laptop user, benefits from being able to access a myriad of communication networks without having to undergo the time-consuming and all-too-often daunting task of reconfiguring their host in accordance with network specific configurations. From another perspective, the network service provider benefits from avoiding "on-site" visits and/or technical support calls from the user who is unable to properly re-configure the portable computer. In this fashion, the gateway device is capable of

providing more efficient network access and network maintenance to the user/subscriber and the network operator.

Gateway devices are typically used to provide network access to the remote portable computer user, such as users in hotels, airports and other locations where the remote portable computer user may reside. Additionally, gateway devices have found wide-spread use in multi-resident dwellings as a means of providing the residents an *intranet* that networks the residents, broadband Internet access capabilities and the capacity to adapt to the variances of the resident's individual enterprise network needs. With the advent of even smaller portable computing devices, such as handhelds, PDAs, and the like, the locations where these users may reside becomes almost limitless. Someday we can envision wireless communications technology providing the capability to offer networking to all forms of land and air passengers. Gateway devices will likely provide the impetus for granting remote network access to all remote users communicating through wireless links and other foreseeable communication mediums.

In most of the remote user applications and the multi-resident dwelling applications, the gateway administrator (i.e. the network service provider) is not so much concerned with "who" the user/subscriber is, but rather, "where" the user resides or is located. Location based information is imperative to the network service provider who desires to manage and bill subscribers based on where they are physically located rather than who they are or what host they may choose to use. For example, in the hotel scenario, the network service provider is more concerned with knowing that Room 301 has a seven day network subscription than knowing who the individual users are that are residing in Room 301. In this manner, the gateway administrator is able to provide Room 301, as opposed to individual residents in Room 301, with a location identifier. The gateway administrator or network provider relies on this information for ensuring accurate subscriber billing.

Additionally, the gateway administrator may benefit from location-based identification in the area of network management. For instance, by classifying within the network databases according to location the gateway device is able to provide network options to subscribers based upon where they are located. By way of example, if the gateway device has "learned" through location identification that Room 301 is a suite, thereby affording its customers additional service privileges, the

gateway device can provide these additional service privileges without the need to query the user/subscriber regarding suite status. The same type of location classification can be beneficial in the multiple-resident dwelling example (i.e. a specially classified building or wing), in the airport example (i.e. a specially designated network port area for first class travelers) or in any other network application that uses a gateway device to provide network access and network adaptation.

SUMMARY OF THE INVENTION

The present invention comprises a method and apparatus for implementing location-based identification in a communication network.

In one embodiment of the present invention a method for implementing location-based identification in a communication network comprises establishing a network connection between a host and a network, transmitting data packets from the host through a location-specific connection port and identifying the port at an access concentrator in the form of a port identifier. The port identifier is then communicated to a network device, typically a gateway device, and stored in a database in communication with the network device.

In another embodiment of the method for location-based identification the process of identifying the port at an access concentrator further includes tagging the network packets at the access concentrator with a port identifier that corresponds to a media access control (MAC) address. The access concentrator and the network device will tag and communicate port numbers by assigning VLAN (Virtual Local Area Network) identifiers to the ports.

In a further embodiment of the method for implementing location-based identification the process of identifying the port at an access concentrator further includes transmitting a port identifying query from a network device, typically a gateway device, to an access concentrator and sending a port identifying response from the access concentrator to the network device. The network device and the access concentrator will have corresponding agents configured to send and respond to queries. For example the gateway device and access concentrator may incorporate an SNMP agent or an XML agent to communicate via queries.

In another embodiment of the invention a network apparatus is defined that is capable of communicating with an access concentrator to determine the port identity

corresponding to the received MAC address. The gateway device is then able to use the location-based identities to structure billing schemes and manage the overall network that the service provider has established.

The invention is further defined in a method for using location-based identification in a communications system. A network device, typically a gateway device accesses a database to determine the identification status of connection ports within a communications network. The identification status of the connection ports are then used to execute a network system application such as billing, authentication or any other network management application.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a block diagram of a communication system that includes a gateway device for automatically configuring one or more hosts to communicate via the gateway device with other networks or other online services.

Figure 2 is a block diagram of a simplified communication network configured so as to allow for location-based identification, in accordance with an embodiment of the present invention.

Figure 3 is a block diagram of a communication network using DSL as the communication medium and implementing VLAN tagging to incorporate location-based identification, in accordance with an embodiment of the present invention.

Figure 4 is a block diagram of a communication network highlighting the unique VLAN identification feature of VLAN tagging, in accordance with an embodiment of the present invention.

Figure 5 is a block diagram of a communication network using DSL as the communication medium and implementing SNMP querying to incorporate location-based identification, in accordance with an embodiment of the present invention.

Figure 6 is a flow diagram of a general method for location-based identification in a communication network, in accordance with an embodiment of the present invention.

Figure 7 is a flow diagram of a method for location-based identification in a communication network implementing VLAN tagging, in accordance with an embodiment of the present invention.

Figure 1 is a flow diagram of a method for location-based identification in a communication network implementing SNMP querying, in accordance with an embodiment of the present invention.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

Referring now to Figure 1, a network system **10** that includes a gateway device **12** is depicted in block diagram form. The network system typically includes a plurality of computers/hosts **14** that access the system in order to gain access to networks or other online services. For example, the hosts can be in communication with ports that are located in different rooms of a hotel or a multi-dwelling residence. Alternatively, the hosts can be in communication with ports in an airport, an arena, or the like. The network system also includes a gateway device that provides an interface between the plurality of hosts and the various networks or other online services. Most commonly, the gateway device is located proximate the hosts at a relatively low position in the structure of the overall network system. (i.e. the gateway device will be located within the hotel, multi-unit residence, airport, etc.) However, the gateway device can be located at a higher position in the overall network system such as at a Point of Presence (PoP) or a Network Operating Center (NOC), if so desired.

Although the gateway device can be physically embodied in many different fashions, the gateway device typically includes a controller and a memory device in which commands are stored that define the operational characteristics of the gateway device. Alternatively, the gateway device can be embedded within another network device, such as an access concentrator or a router, or the commands that define the functioning of the gateway device can be stored on a PCMCIA card that can be

executed by one or more hosts in order to automatically configure the host(s) to communicate with a different network.

The network system **10** also typically includes an access concentrator **16** positioned between the hosts **14** and the gateway device **12** for multiplexing the signals received from the plurality of communications onto a link to the gateway device. Depending upon the medium by which the hosts are connected to the access concentrator, the access concentrator can be configured in different manners. For example, the access concentrator can be a digital subscriber line access module (DSLAM) for signals transmitted via regular telephone lines, a cable modem termination system (CMTS) for signals transmitted via coaxial cables, a wireless access point (WAP) for signals transmitted via a wireless network, a switch or the like. As also shown in Figure 1, the network system typically includes one or more routers **18** and/or servers (not shown in Figure 1) in communication with a plurality of networks **20** or other online services **22**. While the network system is depicted to have a single router, the network system will typically have a plurality of routers, switches, bridges, or the like that are arranged in some hierarchical fashion in order to appropriately route traffic to and from the various networks or other online services. In this regard, the gateway device typically establishes a link with one or more routers. The routers, in turn, establish links with the servers of other networks or other online service providers, such as internet service providers, based upon the subscriber's selection.

The gateway device **12** is specifically designed to adapt to the configuration of each of the hosts **14** that log onto the network system **10** in a manner that is transparent to the subscriber and the network. In the typical network system that employs dynamic host configuration protocol (DHCP) service, an IP address is assigned to the host that is logging onto the network through communication with the gateway device. The DHCP service can be provided by an external DHCP server **24** or it can be provided by an internal DHCP service located within the gateway device. Upon opening their web browser or otherwise attempting to access an on-line service, the gateway device will direct the subscriber to enter some form of an identifier such as their ID and password. In an alternate embodiment of the device, it is anticipated that the gateway device will be able to automatically detect this information upon connection of the host to the network or any attempt to log in. The gateway device

then determines if the subscriber is entitled to access the communication system, the level of access and/or the type of services to which the subscriber is entitled according to an Authentication, Authorization and Accounting (AAA) procedure that is described by U.S. Patent Application Nos. 08/816,174, 09/458,602 and 09/458,569, previously incorporated by reference. An AAA service, which is a database of subscriber records, may be an AAA server remote to the gateway device or the AAA service may comprise a database incorporated into the physical embodiment housing the gateway device.

Assuming that the subscriber has been authenticated and has authorization, the gateway device typically presents subscribers with a home page or control panel that identifies, among other things, the online services or other communication networks that are accessible via the gateway device. In addition, the home page presented by the gateway device can provide information regarding the current parameters or settings that will govern the access provided to the particular subscriber. As such, the gateway administrator can readily alter the parameters or other settings in order to tailor the service according to their particular application. Typically, changes in the parameters or other settings that will potentially utilize additional resources of the network system will come at a cost, such that the gateway administrator will charge the subscriber a higher rate for their service. For example, a subscriber may elect to increase the transfer rate at which signals are transmitted across the communication network and pay a correspondingly higher price for the expedited service.

The home page also permits the subscriber to select the network **20** or other online services **22** that the subscriber wishes to access. For example, the subscriber can access the enterprise network on which the host is typically resident.

Alternatively, the subscriber can access the internet or other on-line services. Once the subscriber elects to access a network or other online service, the gateway device establishes appropriate links via one or more routers **18** to the desired network or online service.

Thereafter, the subscriber can communicate freely with the desired network **20** or other online service **22**. In order to support this communication, the gateway device **12** generally performs a packet translation function that is transparent to the user/subscriber and the network. In this regard, for outbound traffic from the host **12** to the communication network or other on-line service, the gateway device changes

attributes within the packet coming from the user/subscriber, such as the source address, checksum, and application specific parameters, to meet the criteria of the network to which the user/subscriber has accessed. In addition, the outgoing packet includes an attribute that will direct all incoming packets from the accessed network to be routed through the gateway device. In contrast, the inbound traffic from the accessed network or other online service that is routed through the gateway device, undergoes a translation function at the gateway device so that the packets are properly formatted for the user/subscriber's host. In this manner, the packet translation process that takes place at the gateway device is transparent to the host, which appears to send and receive data directly from the accessed communication network. Additional information regarding the translation function is provided by United States Patent Application No. 08/816,714. By implementing the gateway device as an interface between the user/subscriber and the communication network or other online service, however, the user/subscriber will eliminate the need to re-configure their host upon accessing subsequent networks.

In one embodiment of the present invention, the gateway device implements location-based identification. In accordance with the present invention location-based identification may also be embedded within another network device, such as an access concentrator or a router, or the commands that define location-based identification can be stored on a PCMCIA card that can be executed by one or more hosts in order to identify the ports from which the hosts access the network system. Location based identification allows the network system to grant network access to a specific location (e.g. a hotel room, a specific apartment address, etc.) rather than a specific user or host residing at the location. Basing identification on location, as opposed to user or host, allows the gateway administrator (i.e. network service provider) to manage the network system according to user locations and to provide for a billing scheme according to user locations. For an example of a network management system that utilizes location based management in a gateway device environment see United States Patent Application No. __/__,__ entitled "Systems and Methods for Enabling Network Gateway Devices to Communicate with Management Systems to Facilitate Subscriber Management" filed on October 20, 2000 in the name of inventors Short et.al. and assigned to the same assignee as the present invention. That application is herein expressly incorporated by reference as if set forth fully herein.

In one embodiment of the present invention the gateway device includes a processor that communicates with an access concentrator to determine connection ports of host-generated data packets. Once the connection ports are determined they are stored within a database, such as a connection table, that is in communication with the gateway device processor. In a typical gateway device the processor will employ the use of VLAN protocol as the communication link between the gateway device and the access concentrator. While VLAN is by definition, Virtual Local Area Network, in the context we are concerned with VLAN is the IEEE-standard protocol 802.1 Q used to implement VLAN. VLAN technology is well known in the art and has been used to create virtual networks by employing VLAN processors between network interfaces to logically bridge networks together. VLAN works on the concept of tracking ports by tagging the IP packet with an identifier. By using VLAN technology, the gateway device can provision subscriber access to the network on a localized port basis. For example, in a multi-resident dwelling environment, a network service provider may want to provision Internet access to individual units or apartments; each unit is assigned a VLAN ID (a port-location tag). In this example, a resident within the unit can choose to subscribe to the service and the gateway device will then allow Internet access from the resident's unit, regardless of which host or who the user is within the unit. Typically, hosts are granted network access via a MAC (Media Access Control) address that connects the device to a shared network medium. The use of VLAN tagging overrides the MAC address identification process.

VLAN ports can be "tagged" at any level, for example, a specific room in a hotel or an apartment building can be assigned a tag, or a floor within a building, a wing within a building or the building itself may be assigned an individual tag. Alternatively, multiple ports may be tagged to a single room. The gateway device uses a port-location authorization table to manage the assigned ports and ensure accurate billing for services used by a particular port.

Figure 2 illustrates a simplified network system 50 configured so as to allow for location-based identification supported by VLAN tagging. A series of portable computers/hosts 52 are located within separate entities. The separate entities may include apartment units, hotel rooms, airport kiosks, retail outlets or the like. The user (not shown in Figure 2) connects to the network service provider via a port 54 in the

room. The communication between the host and the port may be physical; such as cable to connector, or the communication may be wireless. A modem (not shown in Figure 1), either internal within the hosts or external, may be required to provide access to the network service provider. The medium used to establish the connection may include standard telephone dial-in, cable, CAT5 high quality cable, DSL (Digital Subscriber Line), wireless or any other applicable connection medium.

Once the host establishes connections it begins sending out standard IP (Internet Protocol) packets. An access concentrator 56 initially receives the IP packets. The access concentrator serves as a switch that multiplexes signals received from numerous ports and sends them out one output port. Depending upon the medium by which the hosts are networked to the access concentrator, the access concentrator can be configured in different manners. For example, the access concentrator can be a digital subscriber line access module (DSLAM) for signals transmitted via regular telephone lines, a cable modem termination system (CMTS) for signals transmitted via coaxial cables, a wireless access point (WAP) for signals transmitted via a wireless network, a switch or the like. For VLAN tagging to be implemented the access concentrator must be able to support VLAN technology. If the access concentrator does not support VLAN tagging or a similar tagging means then location-based identification may be implemented by the alternative SNMP (Simple Network Management Protocol) query embodiment of the present invention that is detailed in later discussion herein. Access concentrators are well known by those of ordinary skill in the art and most DSLAMs or other access concentrators will support VLAN technology.

In the VLAN tagging embodiment of the present invention once the access concentrator receives the IP packet it knows what host sent it (from the MAC address header) but it does not know where the host is located. The access concentrator through the use of a VLAN processor has the capability to "know" from what port each packet arrived. It then re-configures the packet by adding a header, typically between the Ethernet and IP portions of the packet according to the 802.1Q IEEE VLAN protocol, identifying the port number and the host. These packets are then forwarded via the single output to the gateway device 58. The gateway device removes the port information and records the data in a database, such as a connection table. A typical connection table maps a port identifier to a MAC address for all

incoming packet routed from the access concentrator. The dynamic nature of the table would allow for the subscriber to change locations and access the network system through an alternate port that has been identified and authorized for use. Once the port number is recorded the VLAN portion is stripped from the packet header and the packet is forwarded on to a router 60 and subsequently the Internet 62 or another network in the system. The VLAN tag may be placed back on a packet that is being communicated from the network to the host so that the access concentrator knows where the packet is to be sent. Additionally, tagging packets coming from the network back to the subscriber provides the gateway device to be interoperable with most access concentrators that are in VLAN tagging mode. This allows for the access concentrators that comprise a composite communication network to communicate in "trunked" line fashion.

It should be noted that while other devices in the network system may communicate in VLAN protocol, in this embodiment the only two devices that require VLAN protocol communication are the access concentrator and the gateway device. The host devices are generally incapable of communicating in VLAN and the downstream network components (routers, switches, bridges, etc.) are inconsequential in this regard.

Figure 3 is a block diagram that illustrates a network configuration using DSL as the communication medium and VLAN tagging as a means of incorporating location-based identification. This networking configuration is shown by way of example, and other communication medium, such as cable, wireless or the like, may also be used to configure a network using VLAN tagging to incorporate location-based identification. The network system 80 includes hosts 82, typically portable computers and in this illustration conventional laptop computers. The hosts in this example are located in individual hotel rooms, however the hosts could be located in other entities, such as apartment units, office rooms, airport kiosks or the like. The hosts access the network via a digital subscriber line (DSL) modem 84. Once a communication link is established the hosts send out standard IP packets 86 to communicate data within the network. At the DSL modem a DSL header is attached to the packets, resulting in the DSL/Ethernet/IP packet 88. The DSL header serves to identify the DSL modem or the port. The packets are then routed through a

connection point shown in this example as punchdown block 90, before an access concentrator 92 receives them.

In this embodiment the access concentrator is a DSLAM that is capable of communicating in VLAN (IEEE 802.1Q) protocol. The access concentrator determines the port from which the packet was sent and assigns an appropriate VLAN identification number to the packet based upon the port from which it was sent. As shown in Figure 4 each port, in this example each hotel room has a unique VLAN ID. For example, hotel room 3210 may be assigned VLAN ID 3210 and hotel room 1001 may be assigned VLAN ID 1001. A table within the access concentrator maps VLAN IDs to the associated room number, kiosk number, etc. A VLAN header is added to the packet, resulting in the Ethernet over VLAN over IP packet 94 shown in Figure 4. These packets are then communicated to the gateway device 96 where the VLAN portion of the header is removed and the VLAN ID is referenced to a specific port within a communications table database associated with the gateway device. In turn, the gateway device may use this location-based identification for billing purposes, such as the Hotel PMS system 98 shown in Figure 4, network authorization or other network purposes. After the gateway device has logged the port related information the packets are communicated forward to other networks, such as the Internet 100. In this instance the packets are communicated as standard IP packets 102.

It should be noted that the gateway device or any other network device implementing location-based identification will require configuration upon initial installation to accommodate location-based identification. If VLAN tagging is to be the basis for location-based identification the gateway device or similar network device must be configured to allow for this communication to occur. A gateway administrator will need to configure the gateway so that VLAN ID's are assigned to individual entities or ports (i.e. room numbers, apartment units, etc.). Port location assignments can be added, updated or deleted according to gateway administrator commands. Adding a port-assignment to the gateway device database may involve assigning a port number, assigning a location to the port number and a conditional state for this port-location. Conditional states may be associated with billing schemes. For instance port-locations may be assigned a "no charge" state, a "charge for use" state, a "blocked" state or any other state may be assigned.

In another embodiment of the present invention, location-based identification is implemented by the processor within a gateway device using a query agent capable of requesting identification data related to the connection port of host-generated data packets. A typical gateway processor will implement SNMP (Simple Network Management Protocol) querying or a similar querying agent may be implemented. The SNMP query embodiment is generally used if the access concentrator does not support the VLAN protocol. Figure 5 is a block diagram that illustrates a network configuration using DSL as the communication medium and SNMP queries as a means of incorporating location-based identification. This networking configuration is shown by way of example, other communication medium, such as cable, wireless or the like, may also be used to configure a network using SNMP queries to incorporate location-based identification. The network includes hosts, typically portable computers and in this illustration conventional laptop computers. The hosts in this example are located in individual hotel rooms, however the hosts could be located in other entities, such as apartment units, office rooms, airport kiosks or the like. The hosts access the network via a digital subscriber line (DSL) modem. Once a communication link is established the hosts send out standard IP data packets, to communicate data within the network. At the DSL modem a DSL header is attached to the packets, resulting in the DSL/Ethernet/IP packet. The packets are then routed through a connection point, shown in this example as punchdown block, before an access concentrator receives them.

In this application, since the access concentrator does not implement VLAN tagging, the packets communicated between the access concentrator and the gateway device are standard IP packets. The IP packets that are received by the gateway device are devoid of any information related to location (i.e. ports). As shown in Figure 5, the gateway device must be configured to send out SNMP query packets back to the access concentrator asking the concentrator from which port did this packet (i.e. this MAC address) come from. The access concentrator that is in communication with a database that ties MAC addresses to ports, is then able to reply to the query with an SNMP query response that ties the MAC address of the packet to a port number. The access concentrator responds by sending an IP packet back to the gateway device identifying the port number. The gateway removes the port number and associated MAC address from the SNMP header and tables the

information in an appropriate communications table database associated with the gateway device. In turn, the gateway device may use this location-based identification for billing purposes, such as the Hotel PMS system **130** shown in Figures 5 and 6, network authorization or any other network purpose. Once the database has proper port number to MAC address mapping for any specific location, the gateway device will no longer be required to send out SNMP queries to the access concentrator. In this manner, the SNMP query procedure is typically only required to be performed once for any given port. After the gateway device has logged the port related information into the database the packets are communicated forward to other networks, such as the Internet **132**. In this instance the packets are communicated as standard IP packets **134**.

It should be noted that in the SNMP query embodiment the gateway device and the access concentrator must be SNMP compatible. Both the gateway device and the access concentrator must be configured with the SNMP agent to receive, send and act upon SNMP queries. If other querying agents are used to implement location-based identification then both the gateway device or a similar network device and the access concentrator must be configured with the chosen querying agent.

In accordance with an embodiment of the present invention, a method for implementing location-based identification in a communication network is shown in the flow chart diagram of Figure 6. At step **150**, a network connection is established between a host and a network. The communication medium that may be used to establish the connection includes telephone line, DSL, conventional cable, CAT5 cable, wireless and the like. At step **160**, data packets, typically IP data packets are transmitted from the host to the network through a location-specific connection port. The location-specific connection port is typically located in a hotel room, an airport kiosk, an apartment building or a similar remote locale. At step **170**, the location-specific connection port is identified at an access concentrator. The identification process that occurs at the access concentrator may include VLAN tagging of the data packets, SNMP query responses or a similar identification process. Once the location-specific connection port has been identified in the form of a port identifier it is then, at step **180**, communicated to a network device, typically a gateway device. The network device will either comprise or be in communication with a database that,

at step 190, stores the port identifiers in order to identify the ports that have been authorized network access.

In accordance with another embodiment of the present invention, a method for location-based identification implementing VLAN tagging in a communication network is shown in the flow diagram of Figure 7. At step 200, a network connection is established between a host and a network. The communication medium that may be used to establish the connection includes telephone line, DSL, conventional cable, CAT5 cable, wireless and the like. At step 210, the host sends network data packets to the network via a connection port and at step 220 the network data packets are received at an access concentrator. The access concentrator may comprise a digital subscriber line access module (DSLAM) for signals transmitted via regular telephone lines, a cable modem termination system (CMTS) for signals transmitted via coaxial cables, a wireless access point (WAP) for signals transmitted via a wireless network, a switch or the like. The access concentrator will be configured with an agent that allows for port identification. For example, an access concentrator may be configured with a VLAN agent that provides for VLAN tagging of the packets transmitted from a location-specific connection port.

At step 230, the access concentrator tags the network data packet with a port identifier that corresponds to the media access control (MAC) address. The tagging of the network data packet is typically performed using VLAN technology. Each port in the network service provider's entity is configured as a virtual LAN and therefore, each port has its own VLAN identifier. At step 240, the tagged data packet is received at a network device, typically a gateway device, where the port identifying information is removed from the packet header. At step 250 the port identifier is incorporated into a database that is in communication with the network device. Once the location-based data, in this instance the port identifier, is incorporated into the database it can be called upon for billing scheme purposes, authentication purposes or for any other use in overall network management systems.

In accordance with another embodiment of the present invention, a method for location-based identification implementing querying in a communication network is shown in the flow chart diagram of Figure 8. At step 300, a network connection is established between a host and a network. The communication medium that may be used to establish the connection includes telephone line, DSL, conventional cable,

CAT5 cable, wireless and the like. At step 310, the host sends network data packets to the network via a connection port and at step 320 the network packets are received at a network device, typically a gateway device.

5 The network device is typically configured with an agent that is capable of generating queries to other network devices. For example the network interface device may be configured with a SNMP agent that is capable of generating SNMP queries or another similar agent, such as XML, may be used. At step 330 the network device sends a port identifying query to an access concentrator, in response to receiving the network data packets. The access concentrator may comprise a digital
10 subscriber line access module (DSLAM) for signals transmitted via regular telephone lines, a cable modem termination system (CMTS) for signals transmitted via coaxial cables, a wireless access point (WAP) for signals transmitted via a wireless network, a switch or the like. Characteristically, the access concentrator will have an agent capable of responding to the queries sent by the network interface device. For
15 example, the access concentrator may be configured with a SNMP agent that is capable of generating SNMP responses, or another similar agent, such as XML, corresponding to the agent used in the network interface device may also be used. Additionally, the access concentrator is configured so as to track port identity versus MAC address of incoming packet traffic.

20 At step 340, the access concentrator sends a port identifying response back to the network device and at step 350 the port identifier is incorporated into a data base that is in communication with the network device. Once the location-based data, in this instance the port identifier, is incorporated into the database it can be called upon for billing schemes, authorization or for use in any other overall network management
25 system.

The method and apparatus of the present invention provide for location-based identification of subscribers as opposed identifying subscribers based on the user or the device. In this manner the network system can administer billing schemes and network management (i.e. quality of service, billing maintenance, authorization, etc.)
30 based upon the physical entity; the hotel room, the apartment unit, the airport kiosk, etc. where the user is located. This provides more options to the network service provider in terms of billing and network management.

Many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings.

Therefore, it is to be understood that the invention is not to be limited to the specific
5 embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limiting the scope of the present invention in any way.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220